

PRODUCT SPECIFICATION

Radiating Coaxial Cable

HQ 50S-78

PRODUCT DESCRIPTION

- The cable is used as a distributed antenna to provide communications in tunnels, subway mines, large building complexes, and any other application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment and can be designed individually.
- With the broadband capability of 75~3000MHz, this cable is used for both one-way and two-way communication systems, and a single radiating cable can handle multiple communication systems simultaneously.



CONSTRUCTION

Inner conductor	Smooth copper tube	Φ 8.70mm
Insulation	Physically foamed PE	Φ22.50mm
Outer conductor	Corrugated copper tube with single row milled slots	Φ 24.90mm
Jacket	Non-halogenated, fire retardant PE	Φ 27.30mm

MECHANICAL PROPERTIES

Minimum bending radius	mm	140
Tensile force	N	1500

ELECTRICAL PROPERTIES

Impedance	Ω	50±2
Capacitance	pF/m	75
Propagation velocity	%	88
DC breakdown voltage	kV	10
Insulation resistance	MΩ•km	>10000

PRODUCT SPECIFICATION

Radiating Coaxial Cable

HQ 50S-78

TRANSMISSION PROPERTIES

Frequency MHz	Nom. attenuation @20 °C, dB/100m	Coupling loss(50%/95%) @20 °C, dB
150	1.80	66 / 76
450	3.60	72 / 80
900	5.10	74 / 85
1800	7.60	80 / 87
2400	9.00	78 / 88

Attenuation & Coupling loss test method : IEC 61196-4.

VSWR

Tested in customers' operating band ≤1.3

ENVIRONMENTAL PROPERTIES

Recommended storage temperature	°C	-70~+85
Recommended installation temperature	°C	-25~+60
Recommended operating temperature	°C	-40~+85