

PRODUCT SPECIFICATION

Trunk Cable

HQ 715

PRODUCT DESCRIPTION



- The high-performance of attenuation allows coaxial cable to be used in various broadband networks.
- Outstanding flexibility, reliability, and cost effectiveness.
- Lower VSWR and perfect shielding effectiveness lead to fewer energy loss and outer interference.

CONSTRUCTION

| | | |
|-----------------|--------------------------------|-----------|
| Inner conductor | Copper clad aluminum | Φ 4.22mm |
| Insulation | Physically foamed PE | Φ 17.42mm |
| Outer conductor | Argon arc welded aluminum tube | |
| Jacket | Black PE | Φ 19.94mm |

MECHANICAL PROPERTIES

| | | |
|-------------------------------|----|--------------|
| Cable length | m | 500/750/1000 |
| Min. bending radius, standard | mm | 200 |
| Min. bending radius, bonded | mm | 127 |
| Max. tensile force | N | 1540 |

ELECTRICAL PROPERTIES

| | | |
|------------------------|-------|--------------|
| Impedance | Ω | 75±2 |
| Propagation velocity | % | 87 |
| Capacitance | pF/m | 50 |
| Jacket spark test RMS | kV | 5.0 |
| Insulation resistance | MΩ•km | >5000 |
| Screening attenuation | dB | ≥110 |
| Structural return loss | dB | 24@5~1000MHz |

PRODUCT SPECIFICATION

Trunk Cable

HQ 715

ATTENUATION

| Frequency MHz | Attenuation @20 °C, dB/100m | Attenuation @20 °C, dB/100ft |
|------------------|--------------------------------|---------------------------------|
| 5 | 0.36 | 0.11 |
| 55 | 1.18 | 0.36 |
| 211 | 2.43 | 0.74 |
| 250 | 2.66 | 0.81 |
| 270 | 2.76 | 0.84 |
| 300 | 2.92 | 0.89 |
| 330 | 3.12 | 0.95 |
| 350 | 3.18 | 0.97 |
| 400 | 3.44 | 1.05 |
| 450 | 3.67 | 1.12 |
| 500 | 3.90 | 1.19 |
| 550 | 4.10 | 1.25 |
| 600 | 4.30 | 1.31 |
| 750 | 4.89 | 1.49 |
| 870 | 5.38 | 1.64 |
| 1000 | 5.84 | 1.78 |
| 1218 | 6.43 | 1.96 |

Attention values may be with a tolerance of ±5%.

ENVIRONMENTAL PROPERTIES

RoHS 2011/65/EU

Compliant