

PRODUCT SPECIFICATION

75 Ohm Drop Coaxial Cable

RG11

PRODUCT DESCRIPTION



- The high-performance of electric properties, which lead to fewer energy loss and outer interference, allow cable to be used as drop cable in terms of broadband, such as digital transmission, television signal, public computer network connection, and so on.
- Indoor and outdoor distribution.

CONSTRUCTION

Inner conductor	Copper clad steel or copper wire	Φ 1.63mm
Insulation	Physically foamed PE	Φ 7.11mm
1st Outer conductor	Bonded aluminum laminated tape	
2nd Outer conductor	Al-Mg or copper alloy braid Coverage: ≥60%	
3rd Outer conductor	Aluminum laminated tape	
4th Outer conductor	Al-Mg or copper alloy braid Coverage: ≥40%	
Jacket	PVC, PE or flame retardant PVC, PE	Φ 10.34mm

MECHANICAL PROPERTIES

Cable length	m	305
Min. single bending radius	mm	50
Pulling strength	N	384
Adhesion Force	N	>60

ELECTRICAL PROPERTIES

Impedance	Ω	75±3
Nominal Capacitance	pF/m	54
Propagation velocity	%	84
DC breakdown voltage	kV	4.0
Insulation resistance	MΩ•km	≥5000
Screening attenuation	dB	≥95@30~1000MHz

PRODUCT SPECIFICATION

75 Ohm Drop Coaxial Cable

RG11

TRANSMISSION PROPERTIES

Frequency MHz	Attenuation @20°C,dB/100m	Attenuation @20°C,dB/100ft
55	3.15	0.96
211	6.23	1.90
300	7.38	2.25
450	9.02	2.75
550	9.97	3.04
750	11.97	3.65
865	13.05	3.98
1000	14.27	4.35

STRUCTURE RETURN LOSS

5-1000MHz	dB	≥20
-----------	----	-----

STANDARDS

2011/65/EU	Compliant
------------	-----------